

Measuring adapter, 5-pole voltage and current

111.7042

- ▶ **Measuring adapter with 32A plug and coupling. For tapping voltages and current.**



1. Use

This adapter cable can be used for devices with a maximum current of 32 A. The voltage can be measured by safety sockets. Current measuring is possible with current clamps.

2. Structure

A fully insulated housing is mounted between a 32 A coupling and a 32 A plug. The 5 measuring sockets for L1, L2, L3, N and PE are located into this housing. The voltages can be measured directly by PQ-Box. Furthermore there are five gaps for current measuring. There the current may be measured by current clamps.

3. Technical Data

Voltage:	400 V
Plug:	32 A
Socket:	4 mm
Protection class:	400V, CAT III

We take care of it.

4. Ordering Information

FEATURE	ORDER CODE
Measuring adapter, 5-pole ● Measuring adapter, 5-pole, safety socket 4mm, 400V, 32A, CAT III	111.7042

A. Eberle GmbH & Co. KG

Frankenstraße 160
D-90461 Nürnberg

Tel.: +49 (0) 911 / 62 81 08-0
Fax: +49 (0) 911 / 62 81 08 96
E-Mail: info@a-eberle.de

<http://www.a-eberle.de>

Version: 11/6/2017 4:02 PM

Copyright 2013 by A. Eberle GmbH & Co. KG
Subject to change without notice.